

Casted mini transformer for printed circuits

Scale	Capacity VA	Gauges in ca. mm										Weight			
		a	b	c	d	e	f	g	h	i	Effectiveness %	Potential difference %	Cu-Weight ca. kg	Overall weight ca. kg	
UI 30/ 5.5	2	43,7	52,5	16,5	37,5	47,5	2,5	3x5	35,0	4	5	10	0,040	0,120	
UI 30/ 7.5	4	43,7	52,5	18,4	37,5	47,5	2,5	3x5	35,0	4	5	10	0,050	0,150	
UI 30/ 10.5	6	43,7	52,5	21,8	37,5	47,5	2,5	3x5	35,0	4	5	10	0,065	0,180	
UI 39/ 8.0	10	56,6	67,5	21,7	50,0	62,5	2,5	3x5	45,0	4	6	10	0,100	0,286	
U 39/ 10.2	14	56,5	67,5	23,8	50,0	62,5	2,5	3x5	45,0	4	6	10	0,130	0,320	
UI 39/ 13.5	18	56,5	67,5	26,8	50,0	62,5	2,5	3x5	45,0	4	6	10	0,130	0,375	
UI 39/ 17.0	24	56,5	68,0	30,5	50,0	62,5	2,5	3x5	45,0	4	6	10	0,140	0,447	
UI 39/ 21.0	30	56,5	68,0	35,0	50,0	62,5	2,5	3x5	45,0	4	6	10	0,170	0,535	